PETROLEUM PRODUCTS

# Petroleum Coke (Green Total Coke), Low Sulfur




Green (uncalcined) total petroleum coke produced in Turkmenistan to a grade intended for graphitized products such as graphite electrodes. Sulfur and ash are each no more than 0.6 %, volatile matter no more than 11 %, and real density after calcination at 1300 °C for 5 hours is at least 2.08 g/cm³. Total moisture is up to 3 %; it is not a rejection criterion and is used for settlement with the buyer. Pieces smaller than 8 mm make up no more than 60 % of the mass. Supplied in bulk by truck or packed in big bags, minimum one truckload. A quality certificate is issued for each lot.

## SPECIFICATIONS

| | |
|---|---|
| Type | **Green (raw) total petroleum coke** |
| Application | **Production of graphitized products (electrodes)** |
| Sulfur, max | **0,6 %** |
| Ash, max | **0,6 %** |
| Volatile matter, max | **11,0 %** |
| Total moisture, max | **3,0 %** |
| Real density after calcination at 1300 °C (5 h), min | **2,08 g/cm³** |
| Pieces smaller than 8 mm, max | **60 %** |
| Packing | **Bulk in trucks or in big bags** |

MINIMUM ORDER
**1 truckload**

DELIVERY TERMS
**FCA • DAP**

PRICE
**On request — depends on volume and specification**